




Husqvarna FS 309

The FS 300-series includes lightweight and compact floor saws of the range. These saws are ideal for small repair jobs and are very easy to handle. They can be transported in any small vehicle.



LOW VIBRATION ENGINE MOUNT

Patent-pending low-vibration engine mount offering a greater comfort in work.




INTELLISEAL

The patented IntelliSeal blade spindle has four sealed radial bearings for strength and durability. Allows for a minimum of 500 hour maintenance intervals and a 1000 hour limited warranty.



ADJUSTABLE HANDLES

Patent-pending adjustable handles for increased operator comfort. Adjustment allows operator to be positioned closer to cutting side for easier alignment and straighter cuts. Handle can also be folded for transport.



POLY V-BELT

Poly-V belts for optimum power transmission.

Features Husqvarna FS 309

- Adjustable right rear wheel for increased stability.
- Husqvarna's floor saws are robust, well designed and easy to use thanks to features as protective cage, lift bail and cutting depth indicator.
- Patent-pending raise/lower assist system, using gas spring.
- Very light weight (64 / 54 kg), facilitating transport and handling.
- Adjustable handle and extendable right rear wheel for increased stability.
- Patent-pending assisted raise / lower system using gas spring.
- Excellent power transmission to the blade thanks to the Poly-V belt.

TECHNICAL SPECIFICATION

Motor manufacturer	Robin
Motor spec	EX27
Max output (As rated by the engine manufacturer)	6,7 kW / 8,98 hp
Cylinders	1
Number of strokes	4-stroke engine
Cylinder displacement	265 cm ³
Cylinder bore	75 mm
Cylinder stroke	60 mm
Fuel tank volume	6,1 lit
Air filter type	Cyclone dry dual
Starter	Cord
Engine cooling	Air
Belt	Poly V
Number of belts	14
Oil capacity, l	1,1 lit
Output RPM	3600 rpm
Diamond blade, max	350 mm
Max cutting depth	120 mm
Spindle diameter	25,4 mm
Blade depth control	Handwheel
Blade shaft diameter	19,05 mm
Blade flange	114,3 mm
Arbor size	25,4 mm
Axle front	20 mm
Rear axle diameter	20 mm
Handle bars	Multi position
Primary wheel size	Outside diameter: 101,6 Wheel width: 38,1 Inner bore: 15,88 mm
Secondary wheel size	Outside diameter: 152,4 Wheel width: 38,1 Inner bore: 15,88 mm
Blade guard attachment	Bolted
Blade guard type	Bolted
Weight	64 kg
Weight incl. packaging	71 kg
Product size, LxWxH	914,4x381x990,6 mm
Sound power level, guaranteed (LWA)	84 dB(A)
Sound pressure	100 dB(A)
Hand arm vibration (Aeq)	3 m/s ²



6 - 10 Parkway Drive, Mairangi Bay, Auckland 0632
Ph: 09 443 2436 Auck Ph: 03 341 6923 Chch

www.yrco.co.nz